

PERIODIC MAINTENANCE CHART

The maintenance and adjustments must be done in accordance with this chart to keep the motorcycle in good running condition.

Operation/Frequency	Whichever Comes first every	Odometer reading in US Miles *						
		500	3000	6000	9000	12000	15000	18000
Engine oil-change	1 year	+	+	+	+	+	+	+
Oil filter-replace	.	+	.	+	.	+	.	+
Coolant-change	2 years	+
Radiator hoses, connections-check #	1 year	+	.	+	.	+	.	+
Final gear case oil level-check #	.	.	.	+	.	+	.	+
Final gear case oil-change	.	+	+
Propeller shaft sliding joint-lubricate	.	.	.	+	.	.	.	+
Fuel system-clean	.	.	.	+	.	+	.	+
Fuel hose-replace	4 years
Spark plugs-clean and gap #	.	+	+	+	+	+	+	+
Valve clearance-check #	.	+	+	+	+	+	+	+
Air suction valve-check #(US model)	.	.	+	+	+	+	+	+
Air cleaner element-clean	.	.	+	.	+	.	+	.
Air cleaner element-replace	5 cleanings	.	.	+	.	+	.	+
Throttle grip play-check #	.	+	+	+	+	+	+	+
Idle speed-check#	.	+	+	+	+	+	+	+
Carburetor synchronization-check #	N/A	+	+	+	+	+	+	+
Clutch-adjust	.	+	+	+	+	+	+	+
Brake lining wear-check #	.	.	+	+	+	+	+	+
Brake fluid level-check #	Month	+	+	+	+	+	+	+
Brake fluid-change	1 year	.	.	+	.	+	.	+
Brake hose-replace	4 years
Master cylinder cup and dust seal-replace	2 years
Caliper piston seal and dust seal-replace	2 years
Brake play-check #	.	+	+	+	+	+	+	+
Brake light switch-check #	.	+	+	+	+	+	+	+
Steering play-check #	.	+	+	+	+	+	+	+
Steering stem bearing-lubricate	2 years	+	.	.
Front fork oil-change	.	.	.	+	.	+	.	+
Front fork oil seal-clean	.	.	+	+	+	+	+	+
Tire wear-check #	.	.	+	+	+	+	+	+
Wheel bearing-lubricate	2 years	+	.	.
Speedometer gear-lubricate	2 years	+	.	.
Swing arm pivot-lubricate	.	.	.	+	.	+	.	+
Battery electrolyte level-check #	Month	+	+	+	+	+	+	+
General lubrication-perform	.	.	+	+	+	+	+	+
Nut, Bolt, Fastener tightness-check	.	+	.	+	.	+	.	+

* For higher odometer readings, repeat at the frequency interval established here.

Replace, add or adjust if necessary.